

## Specifications:

### GPM-X2 Series, 2-Channel Simultaneous Charger

Quick Charge Current: 1.5A Simultaneous  
Size: 4.5" x 5.5" x 3"  
Weight: 1.0 lbs.  
Input Voltage: 90-240VAC 50/60Hz



## Warranty:

This product is warranted to the Original Purchaser against all defects in material and or workmanship for the period herein.

The warranty period shall be, 3 years for parts and labor, unless otherwise noted. Core SWX agrees to pay equal return freight costs to return the product the same method it was received. In the event of an issue, purchaser agrees to the below RMA procedure.

### Procedure:

1. Go to <http://www.coreswx.com/repairsreturns> and fill out the online form
2. Print the RMA number confirmation, and ship the product needing service to Core SWX, LLC. along with RMA number confirmation, and copy of bill of sale.
3. All shipments must be done either through UPS or FEDEX, and insured if necessary
4. Core SWX, LLC. is not responsible for any lost shipments.

Core SWX reserves the right to repair or replace any defective product under warranty after Core SWX determines which is more practical.

If Core SWX receives defective product for warranty repair and they are found to be defective as a result of misuse or other damage, not caused by normal wear and tear, Core SWX will notify the customer of an estimate of repair. Customer will incur costs. There are no further warranties, either expressed or implied, including warranties of merchantability or fitness for a particular purpose that has any bearing upon this transaction.



## **GPM-X2 Series Brick Battery Charger INSTRUCTION MANUAL**

Thank you for your choice in purchasing a Core SWX style battery charger. The charger is designed to improve and assist you in your battery charging requirements.

Please read this manual to help you understand and capitalize on the features of this charger.

### **Features:**

- This charge is designed for Li-Ion packs solely. When charging two packs, the charger will charge simultaneously at 1.5A per hour charge rate. 98wh packs will charge in approximately 4hours.
- Rugged, sleekly styled, compact charger chassis.
- Automatic Universal AC input for world-wide use.
- Automatic detection of damaged or misused batteries for added safety.

### **Charging Operation:**

- Insert the AC power cord into the AC receptacle in the back of the charger.
- Connect all batteries needing charge into the charger.
- Turn the rear panel power switch to the ON position. At this time the switch will light and the LED lights on the front panel of the charger will blink green when charging.
- If the battery does not meet quick charging conditions(i.e. temperature or deeply discharged) the charger will precharge the battery and go into a trickle charge mode until it is safe to enter quick charge mode.
- The LED corresponding with the charging bay will turn solid green when the battery is fully charged.

### **Notes On Use:**

- While operating the charger do not place anything on the charger or block the ventilation slots.
- An increase in temperature is normal during charging.
- Make sure to firmly connect batteries to the charger mounts and that the contacts are clean.
- The product must be earthed.
- Do not attempt to disassemble the charger, please contact CoreSWX for any service issues.
- The fuse within the AC receptacle can be replaced only with one of the same type and rating. (A spare fuse is included for your convenience)
- Do not operate this device near equipment susceptible to noise(i.e. TV).

### **Compatibility outside of Core SWX battery packs**

- For V-mount, this charger will charge most V-mount, Lithium Ion packs on the market.
- For 3-Stud, this charger will only charge Core SWX packs.